

ICON EDGE

The Icon EDGE is a very compact, feature rich, lightweight, fast beam/spot/wash luminaire. It combines an ultra-bright beam, with sharp gobo projection, a CMY-color mixing system and variable CTO. Fitted with the new Philips Platinum 21R lamp (470W), Icon EDGE outputs an amazing 20,000 Lumens.


Featuring 2-24 degree zoom in beam mode, and 2.5-32 degree zoom in spot mode, eight rotating gobos and 14 fixed, a continuous animation wheel and two prisms the Icon EDGE has a huge amount of creative options. A newly designed system provides extremely smooth, full field dimming.

The fixture can take direct Art-Net input, as well as DMX512. Icon EDGE is a multi-use luminaire, with full animation wheel, beam, spot and wash function in one fixture.



Features:

- 20,000 Lumen output
- Extremely narrow ACL beam with zoom
- Even spot function
- Large Zoom range
- Full 16bit CMY + incl CTO
- 14 + Open fixed colour wheel
- 8 + Open interchangeable rotating gobos
- Custom glass gobo mode available
- 14 + Open fixed Gobo
- Continuous animation wheel
- 2 Prisms (8 facet, linear 4 facet)
- Split colours
- Drop In frost
- Ultra-fast Pan/Tilt movement
- Can be mounted in any orientation



	0	10m	20m	30m
Beam		390.000	110.000	55.000lux
Spot		120.000	26.000	16.000lux
Wash		84.000	25.000	10.000lux

Glass Gobos:

Material: Borofloat, 1.1mm thickness
 Outer Diameter: 16.3mm
 Image Diameter: 9mm

Ensure EDGE is configured on the fixture menu to accept glass gobos when fitting – glass gobos will break if not configured!

Technical Specifications:

Lamp	Philips Platinum 21R
Colour Temperature	7800K
Beam Angle (beam)	2-24°
Beam Angle (Spot)	2.5-32°
Beam Angle (Wash)	3.5-39°
Lumens Output	20.000
Nominal Lifetime	750 hrs
Focus	adjustable focus
Frost	drop-in
Colour wheel	14 + open
CMY	0-100%/ 16bit
CTO	0-100%/ 16bit
Rotating Gobo	8+ open
Indexing Gobo	yes
Fixed Gobo	14+ open
Prism	8 facet + lin 4 facet
Indexing Prism	yes
Animation Wheel	continuous
Indexing Animation Wheel	yes
Shutter/Strobe	variable, 13 flash/sec
Dimmer	0-100%/ 16 bit
Pan/Tilt	540/270°
DMX Control Mode	2 (25, 36 CH)
RDM	yes
Art-Net	yes
Self Charging Battery	yes
Cooling System Monitoring	yes
Wattage	650W
Power	AC100-240V, 50/60hz
Operating Temperature	-10° to +45°c
Certification	CE & cETL
Weight	31kg
Dimensions LxWxH (mm)	453x319x709

Metal Gobos:

Material: 1060 Aluminium/0.5mm thickness
 Outer Diameter: 16.9mm
 Image Diameter: 9mm